



BOPP Packing Tape

Technical Data

Product Description	<p>These tapes are used in electrical insulation purpose, in packaging, sealing and a various other general uses. These tapes are also used for general labelling with printing.</p> <ul style="list-style-type: none">● Bopp film sticky packing tape● Water based acrylic● Custom colors
Product Construction	<p>Backing: Bopp film Adhesive: Acrylic Adhesive Type: Water Activated Feature: Antistatic Design Printing: Offer Printing</p>
Typical Physical Properties	<p>Adhesion To Peel(N/25mm): ≥ 5 Holding Power(Hrs): ≥ 48 Tensile Strength(N/cm): ≥ 30 Elongation(%): ≤ 180</p>
Features	<ul style="list-style-type: none">● Excellent adhesion and shear properties● Resistance to cold, heat and aging● UV stabilized - won't lift off cartons● High mechanical strength and good impact resistance● Ideal for use in dispensers
Application Ideas	<ul style="list-style-type: none">● Shipping, packaging, bundling, wrapping.● Ideal for sealing of cartons, merchandise, pallets● Excellent performer for both hand and machine
Storage	<p>Store under normal conditions of 16°C to 27°C and 40 to 60% R.H.in the original carton.</p>
Shelf Life	<p>To obtain best performance, use this product within 24 months from date of manufacture.</p>
Specifications	<p>Any width, length, thickness of tape is 35mic - 90mic, The most common thickness is between 38mic - 53mic. Brand: Buyer's brand is able to printed on paper core.</p>

Images



DONGGUAN GUANHONG PACKING INDUSTRY CO.,LTD.

FURONGSHA IND.DIST., WANGNIUDUN TOWN, DONGGUAN CITY, G.D.CHINA

TEL: 86-769-88518755 FAX: 88518376 E-MAIL: lucy@dgguanhong.com

We chat /what's app: 0086-13431420003

<http://www.bopppackingtape.com/>